

## AXIS P1367-E Network Camera

Outdoor-ready 5 MP video in all light conditions

The 5 MP resolution at full frame rate ensures great video quality with a high level of details. The innovative outdoor-ready camera P1367-E is built for all weather conditions, with a quick and easy installation in mind. Built-in camera rails enable easier changing of lenses and with a simple roll of the sensor, the format shifts to Axis Corridor Format. In complex lighting or even in the dark, Forensic WDR together with Lightfinder will discover all details. Axis Zipstream technology optimizes the video stream saving bandwidth and storage while maintaining high video quality.

- > **5 MP resolution at 25/30 fps**
- > **Temperature range: -40 °C to 55 °C (-40 °F to 131 °F)**
- > **IK10-, IP66- and NEMA 4X-ratings**
- > **Lightfinder and Forensic WDR**
- > **Zipstream**



# AXIS P1367-E Network Camera

Camera	
Image sensor	1/2.9" progressive scan RGB CMOS
Lens	IR corrected, CS-mount lens, P-Iris Varifocal 2.8–8.5 mm, F1.2 With IK10 protection in the front window: Horizontal field of view: 72°–36° Vertical field of view: 40°–20° Without IK10 protection in the front window: Horizontal field of view: 83°–36° Vertical field of view: 45°–20°
Day and night	Automatically removable infrared-cut filter
Minimum illumination	Color: 0.15 lux B/W: 0.03 lux, at 50 IRE F1.2
Shutter speed	1/55500 s to 2 s
System on chip (SoC)	
Model	ARTPEC-6
Memory	1 GB RAM, 512 MB Flash
Video	
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG Controllable frame rate and bandwidth
Resolution	3072x1728 (5 MP) to 160x90
Frame rate	25/30 fps (50/60 Hz) in all resolutions
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264
Multi-view streaming	Up to 8 individually cropped out view areas
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR: Up to 120 dB depending on scene, white balance, day/night threshold, exposure mode, exposure zones, compression, orientation: 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, dynamic text and image overlay, privacy masks
Pan/Tilt/Zoom	Digital PTZ Uploadable PTZ driver (Pelco D pre-installed)
Audio	
Audio streaming	Two-way, full duplex
Audio encoding	AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM 8/16/32/48 kHz Configurable bit rate
Audio input/output	External microphone input or line input, line output Automatic gain control
Network	
Security	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X (EAP-TLS) <sup>a</sup> network access control, digest authentication, user access log, brute force delay protection, signed firmware
Supported protocols	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS <sup>a</sup> , HTTP/2, TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP <sup>™</sup> , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SFTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)
System integration	
Application Programming Interface	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform, specifications at <a href="http://axis.com">axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF <sup>®</sup> Profile G, ONVIF <sup>®</sup> Profile M, ONVIF <sup>®</sup> Profile S and ONVIF <sup>®</sup> Profile T, specification at <a href="http://onvif.org">onvif.org</a>
Event triggers	Analytics, open casing, edge storage events, external input, audio level, time scheduled MQTT subscribe
Event actions	File upload: FTP, SFTP, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS and TCP External output activation

Video recording to edge storage, Play audio clip  
Pre- and post-alarm video buffering  
PTZ preset, Guard tour, Overlay text  
Day/Night switching, Status LED activation  
MQTT publish  
Send SNMP trap

Data streaming	Event data
Built-in installation aids	Focus assistant, pixel counter, remote back focus
Analytics	
Applications	Included AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, active tampering alarm, audio detection Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>
General	
Casing	IP66-, IP67- and NEMA 4X-rated, IK10 impact-resistant polymer enclosure Color: White NCS S 1002-B
Sustainability	PVC free
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3, max 9.2 W, typical 5.3 W
Connectors	RJ45 10BASE-T/100BASE-TX PoE I/O: 4-pin 2.5 mm terminal block for two configurable inputs/outputs (12 V DC output, max. load 50mA) RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block 3.5 mm mic/line in, 3.5 mm line out i-CS connector (compatible with P-Iris and DC-iris)
Storage	Support for microSD/microSDHC/microSDXC card Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
Operating conditions	-40 °C to 55 °C (-40 °F to 131 °F) Maximum temperature (intermittent): 60 °C (140 °F) Humidity 10–100% RH (condensing)
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Approvals	EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 32 Class A, KCC KN32 Class A, KN35 Safety IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IS 13252 Environment IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, IEC/EN 62262 IK10, IEC/EN 60529 IP67 Network NIST SP500-267
Dimensions	382 x 155 x 120 mm (15 x 6.1 x 4.7 in)
Weight	2.2 kg (4.9 lb)
Included accessories	Installation guide, Windows <sup>®</sup> decoder 1-user license, wall mount bracket, sunshield, connector kit IK10 tool
Optional accessories	Axis mounts, Axis lenses, Axis midspans For more accessories, see <a href="http://axis.com">axis.com</a>
Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://axis.com/warranty">axis.com/warranty</a>

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit ([openssl.org/](http://openssl.org/)), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).

Environmental responsibility:

